



## PT-100 CHARGE CONTROLLER

### *Maximize Energy Harvest and Improve Battery Life*

#### Model Numbers

- PT-100

#### Available For

- Renewable Energy Systems
  - Off-grid Power
  - Back-up Power

#### Works With

- ME Series
- MM-AE Series
- MM-E Series
- MMS Series
- MMS-E Series
- MS Series
- MS-AEJ Series
- MS-E Series
- MSH Series
- MS-PAE Series
- MS-PE Series
- MMP Panel System
- MMP-E Panel System
- MP Panel System
- MP-E Panel System
- RD Series
- RD-E Series

#### Available Configurations

- Works as a stand-alone controller using internal settings
- Works with a Magnum-Dimensions Inverter/Charger and Magnum-Dimensions Remote. Menu settings for the PT-100 are currently only available via the ME-ARC Remote

The PT-100 is a Maximum Power Point Tracker (MPPT) charge controller designed to harvest the maximum available energy from the PV array and deliver it to the batteries. The PT-100's MPPT algorithm finds the maximum power point of the array and operates at this point while regulating the output current to 100 amps and battery voltage to fully charge the battery.

#### Features

- **High Efficiency:** The PT-100 provides higher than 99% conversion efficiency and uses less than two watts of power in nighttime mode.
- **MPPT:** Maximum Power Point Tracking technology for increased PV power output efficiency.
- **Voltage Options:** Compatible with 12, 24, or 48V battery systems with automatic detection of system voltage. The PT-100 will produce up to 100 amps regardless of battery voltage.
- **Supports a Large PV Array:** A single controller supports a large PV array up to 6600W. Larger PV arrays may be used because the PT-100 is current limited to 100 amps for maximum harvest.
- **Optimal Battery Charging:** Automatic battery temperature compensation using an included external temperature sensor for optimum battery charging, even during extreme temperature changes.
- **Multi-stage Charging:** Maximizes system performance and improves battery life.
- **GFDI:** Integrated PV Ground-Fault Detection and Interruption/Indication, with pre-fault leakage/diagnostic metering.
- **LED Indicators and Screen:** Multiple LED indicators and large digital LED screen on front panel for easy-to-read system information.
- **On-site Updates:** The PT-100's software can be updated on site.
- **Extensive Electronic Protection:** Over-temperature protection, power derating when temperature is high, PV short circuit and high PV input shutdown, output overcurrent protection and night-time back-feed (reverse current) protection.
- **AFCI:** An integrated PV Arc-Fault Circuit Interrupter detects, indicates, and extinguishes series arcs. The AFCI is designed to meet the new National Electric Code (NEC) Article 690.11 requirements.
- **Convenient Installation:** Run all of the wiring to the unique, remain-in-place wiring box with ease prior to installing the full PT-100 unit.
- **Easy MP and MMP integration:** The PT-100 is designed to work with a Magnum Panel (MP) or Mini-Magnum Panel (MMP). It provides room and access to PV and battery disconnect breakers.

#### Even More Functionality with the Optional Remote

- Built-in programmable auxiliary relay for device control.
- Internal data logging functionality keeps energy harvest information and battery Ahr/Whr data up to 255 days. Use the optional remote to display this information.

# PT-100 CHARGE CONTROLLER SPECIFICATIONS

PT-100	
<b>ELECTRICAL SPECIFICATIONS</b>	
Maximum PV input voltage (any condition)	200 VDC + battery voltage or 240 VDC - whichever is lower
Maximum PV operating voltage	187 VDC
Maximum PV array short circuit current	100 ADC
Nominal battery voltage range	12, 24, or 48 VDC
Battery charger output voltage range	10 to 66 VDC
Continuous charger output current	100 ADC (from -20 °C to +40 °C) with proportional power reduction up to 60 °C ambient
Maximum output power	6600 watts
Peak (and full power) efficiency	>99% (98% typical)
Tare loss / nighttime power consumption	<2 watts (fan off, display/LEDs off)
Charger regulation method	Automatic three-stage (bulk, absorption, float) charge with manual equalization
<b>GENERAL FEATURES AND CAPABILITIES</b>	
Battery temperature compensation	With Battery Temperature Sensor (BTS) connected (battery temperature -20 °C to +55 °C)
Internal cooling	Using dual ball-bearing fans for long life
Overcurrent protection	With two overlapping circuits
Over-temperature protection	On transformer and MOSFETS
Listings	ETL Listed to UL/cUL 1741, CSA C22.2 #107.1-01, CE
Warranty	Five years parts and labor
<b>ENVIRONMENTAL SPECIFICATIONS</b>	
Operating temperature	-20° C to +60° C (-4° F to 140° F)
Nonoperating temperature	-40° C to +70° C (-40° F to 158° F)
Operating humidity	0 to 95% RH non condensing
<b>PHYSICAL SPECIFICATIONS</b>	
Enclosure type	Indoor, ventilated, with removable powder-coated conduit box
Unit dimensions (w x h x d)	8.5" x 15.5" x 4.0" (21.6 cm x 39.4 cm x 10.2 cm)
Shipping dimensions (w x h x d)	11.5" x 19.5" x 8.125" (29.2 cm x 49.5 cm x 20.6 cm)
Mounting	Mounted on a vertical surface (wall) or installed on MP or MMP enclosure
Weight	12.5 lb (5.7 kg)
Shipping weight	15 lb (6.8 kg)
Max operating altitude	15,000' (4570 m)



## MAGNUM-DIMENSIONS

2211 West Casino Road  
Everett, Washington 98204 USA

425-353-8833

4467 White Bear Pkwy  
St. Paul, MN 55110 USA

800-553-6418

[www.magnumenergy.com](http://www.magnumenergy.com)

Testing for specifications at 25° C.  
Specifications subject to change without notice.